

BUILDING SPECIFICATIONS

General Description

Brookfield Place is one of North America's truly great people places. This landmark is located in the heart of the financial district, and is home to the world's most prestigious financial, commercial and legal firms, as well as the Hockey Hall of Fame.

Brookfield Place is green building certified with a Gold level of certification in the Leadership in Energy and Environmental Design (LEED®) Existing Buildings: Operations and Maintenance program.

Bounded by Bay, Wellington, Yonge and Front Streets, the 5 1/2 acre, 2.6 million square foot complex combines two architecturally stunning office towers with Toronto's oldest intact streetscape, including the award-winning Allen Lambert Galleria - a six storey pedestrian thoroughfare resplendent in light and glass.

Connected to the underground PATH System, Brookfield Place is steps away from major hotels, retail and entertainment centres including Air Canada Centre.



Design Architect	Bregman + Hamann Architects
General Contractor	PCL Constructors Eastern Inc.
Mechanical Engineer	The Mitchell Partner ship (TMP)
Electrical Engineer	Mulvey & Banani
Structural Engineer	M.S. Yolles & Partners Limited
Completion Date	TD Canada Trust Tower Fall 1990 Bay Wellington Tower March 1992 Total Project May 1992
Building Height	TD Canada Trust Tower, 51 storeys Bay Wellington Tower, 47 storeys
Design Load	100 pounds per square foot live load including partition load
Rentable Area	Office 2,418,461 square feet Ground level 65,000 square feet Concourse level 52,000 square feet
Typical Floor Area	Bay Wellington Tower - 26,000 rentable square feet
Ceiling Heights	Slab-to-slab heights on office floors average 13'0" Standard floor to ceiling height is 9'0''
Mullion Spacing	3.5 feet
Mullion Spacing Interior Column Spacing	
Interior Column	3.5 feet
Interior Column Spacing Heating, Ventilation and	3.5 feet Column free The Building Automation and Energy Management System is a Direct Digital Control (DDC) system that monitors and operates > 5000 variable
Interior Column Spacing Heating, Ventilation and Air Conditioning	3.5 feet Column free The Building Automation and Energy Management System is a Direct Digital Control (DDC) system that monitors and operates > 5000 variable air volume (VAV) boxes and utilizes over 40,000 software points. The building's HVAC systems are designed to meet or exceed 1990 Building Code requirements. Design conditions are based upon occupancy of not
Interior Column Spacing Heating, Ventilation and Air Conditioning Design Criteria	Column free The Building Automation and Energy Management System is a Direct Digital Control (DDC) system that monitors and operates > 5000 variable air volume (VAV) boxes and utilizes over 40,000 software points. The building's HVAC systems are designed to meet or exceed 1990 Building Code requirements. Design conditions are based upon occupancy of not more than one person per 200 usable square feet. Heat is supplied by six (6) natural gas fired water tube boilers. Cooling is provided by 8 centrifugal chillers totaling 8,780 tons and Deep Lake Water Cooling through Enwave. Supplemental cooling is available 24 hours a day through a dedicated
Interior Column Spacing Heating, Ventilation and Air Conditioning Design Criteria Heat	3.5 feet Column free The Building Automation and Energy Management System is a Direct Digital Control (DDC) system that monitors and operates > 5000 variable air volume (VAV) boxes and utilizes over 40,000 software points. The building's HVAC systems are designed to meet or exceed 1990 Building Code requirements. Design conditions are based upon occupancy of not more than one person per 200 usable square feet. Heat is supplied by six (6) natural gas fired water tube boilers. Cooling is provided by 8 centrifugal chillers totaling 8,780 tons and Deep Lake Water Cooling through Enwave.
Interior Column Spacing Heating, Ventilation and Air Conditioning Design Criteria Heat Air Conditioning Standard Hours of HVAC	Column free The Building Automation and Energy Management System is a Direct Digital Control (DDC) system that monitors and operates > 5000 variable air volume (VAV) boxes and utilizes over 40,000 software points. The building's HVAC systems are designed to meet or exceed 1990 Building Code requirements. Design conditions are based upon occupancy of not more than one person per 200 usable square feet. Heat is supplied by six (6) natural gas fired water tube boilers. Cooling is provided by 8 centrifugal chillers totaling 8,780 tons and Deep Lake Water Cooling through Enwave. Supplemental cooling is available 24 hours a day through a dedicated tenant condenser system. 7:30 AM to 6:30 PM, Monday through Friday
Interior Column Spacing Heating, Ventilation and Air Conditioning Design Criteria Heat Air Conditioning Standard Hours of HVAC Operation	Column free The Building Automation and Energy Management System is a Direct Digital Control (DDC) system that monitors and operates > 5000 variable air volume (VAV) boxes and utilizes over 40,000 software points. The building's HVAC systems are designed to meet or exceed 1990 Building Code requirements. Design conditions are based upon occupancy of not more than one person per 200 usable square feet. Heat is supplied by six (6) natural gas fired water tube boilers. Cooling is provided by 8 centrifugal chillers totaling 8,780 tons and Deep Lake Water Cooling through Enwave. Supplemental cooling is available 24 hours a day through a dedicated tenant condenser system. 7:30 AM to 6:30 PM, Monday through Friday 9:00 AM to 5:00 PM, Saturday Building-standard power consists of 2.0 watts per square foot lighting,

Number of Passenger Elevators	Full BWT-28 Passenger, 9 Shuttles, 4 Service & 4 Escalators
Passenger Elevator Capacity	3,500 pounds per cab, depending on elevator bank
Passenger Elevator Speed	Capacity to travel up to 1,200 FPM (feet per minute), depending on bank
Number of Service Elevators	Two main service elevators in each tower servicing loading dock to penthouse mechanical
Service Elevator Capacity	Full BWT = 4500 lbs
Service Elevator Size	Full BWT = 8'L x 7'W x 14'H inside elevator

